



SD Aluminium Roofing Screws Range

**Designated Building Product - Class 1
BPIR Declaration** - V1. 08.2025

Declaration

SD Aluminium Limited has prepared this declaration to meet the requirements of Schedule 1(d) of the Building (Building Product Information Requirements) Regulations 2022.

This declaration applies to the [Roofing Screws Range](#) as a designated building product, Class 1.

It confirms that the information provided is based on our technical documentation, manufacturing processes, and supporting evidence, and is, to the best of our knowledge, accurate and complete at the time of publication.

Product / System

- Name* - **SD Aluminium Roofing Screws Range**
Identifier - Hex Washer Head Roofing Screws, Polycarbonate Head Roofing Screws, Hex Washer Head Self Drilling Screws, Hex Washer Head Self Tapping Screws
Line -

Description

The SD Aluminium Roofing Screws range is designed for securing metal or polycarbonate roofing to timber or steel purlins. This group includes hex washer head roofing screws, polycarbonate head roofing screws, self-drilling and self-tapping hex washer head screws, hex washer head screws with Neo Seal, and black electrophoretic steel self-drilling screws. Tip types include self-drilling tips for direct fastening into steel purlins, self-tapping tips for timber structures, and specialised sealing tips for weatherproofing. Many products in this range are supplied with integrated sealing washers to ensure long-term protection against water ingress.

Available in a range of materials and finishes to suit various installation conditions:

- *Stainless Steel 304* – General exterior use in non-coastal areas.
- *Stainless Steel 316* – Harsh and coastal environments requiring maximum corrosion resistance.
- *Hot-Dip Galvanised Steel / Zinc Coated Steel* – General exterior and interior use; avoid prolonged exposure to salt spray.
- *Specialty Coatings* – Coloured or treated finishes for decorative, wear-resistant, or specific environmental applications.

Size Range

- **Hex Washer Head Roofing Screws** - Dia: M5.5-M6.2, Length: 25mm - 100mm,
- **Polycarbonate Head Roofing Screws** - Dia: M5.5, Length: 50mm - 65mm,
- **Hex Washer Head Self Drilling Screws** - Dia: M5.5-M6.15, Length: 25mm - 125mm,
- **Hex Washer Head Self Tapping Screws** - Dia: M5.5-M6.15, Length: 25mm - 125mm



SD Aluminium Roofing Screws Range

BPIR Declaration

Scope Of Use

The Roofing Screws range is suitable for fixing metal or polycarbonate sheets to timber or steel framing in residential, commercial, rural, and industrial buildings. Common applications include:

- *Roof sheet installation – Fastening corrugated, trapezoidal, or other profiled sheets to steel or timber purlins.*
- *Wall cladding – Securing metal or polycarbonate panels in vertical or horizontal orientation.*
- *Accessory installation – Fixing flashings, ridges, barges, and other sheet metal accessories.*
- *Polycarbonate roofing – Using screws with polycarbonate heads or weather seals to prevent cracking and ensure watertight fixing.*

Tip selection should match the substrate and application:

- *Self-drilling tip → For steel or metal-to-metal fastening without pre-drilling.*
- *Self-tapping tip → Cuts its own threads in softer materials, but may need a pilot hole.*
- *Wing tek tip → For fastening timber to steel, enlarges timber hole before engaging steel.*

Installations, Conditions of Use, and Limitations

- All fasteners must be installed into structurally sound timber, steel, or other suitable substrates capable of withstanding the design loads for the intended application.
- For coach screws, drill pilot holes to the manufacturer's recommended diameter to prevent timber splitting and ensure correct thread engagement.
- For bolts, through bolts, and threaded rods, use correctly sized washers and nuts to distribute load evenly and prevent embedment.
- Tighten using suitable tools (wrench, socket, or spanner) and apply torque according to specifications to avoid over-tightening or thread damage.
- Select material grade and coating to match environmental exposure zone and required service life.
- Avoid direct contact with incompatible metals that may cause galvanic corrosion; if unavoidable, use barriers such as nylon washers, sealants, or protective coatings.
- Over-torquing may strip threads, damage substrates, or reduce holding capacity.
- Standard galvanised products are not recommended for severe marine or highly corrosive environments without additional protection.
- Any cutting of galvanised or stainless bolts/rods must be followed by application of corrosion protection to the exposed ends.



SD Aluminium Roofing Screws Range

BPIR Declaration

Relevant Building Code Clauses

B1	Structure	<i>B1.3.1, B1.3.2, B1.3.3(c, f, h, j, m), B1.3.4</i>
B2	Durability	<i>B2.3.1(a), B2.3.2(a, b)</i>
F2	Hazardous Building Material	<i>F2.3.1, F2.3.3</i>

Contributions To Compliance

The SD Aluminium Fastener range contributes to compliance with the following New Zealand Building Code (NZBC) clauses, when installed in accordance with manufacturer instructions and good trade practice:

- *B1 Structure – Provides secure mechanical fixing between timber, steel, masonry, and composite materials. Correct fastener selection and installation ensures the building elements remain stable under expected loads including wind and seismic actions.*
- *B2 Durability – Fasteners are manufactured from galvanised steel, stainless steel, or zinc-coated steel, with optional specialty coatings. When appropriately selected for the environment (interior, exterior, or coastal), the fasteners will remain durable for the minimum 50-year (structural) or 15-year (non-structural) building life as required by the NZBC.*
- *F2 Hazardous Building Materials – Fasteners are made from materials that do not present a health hazard when used as intended.*

Further technical information to support compliance is available from SD Aluminium upon request.

Maintenance Requirements

- To ensure long-term performance and compliance with the intended use, all fasteners should be:
- Inspected periodically – at least once every 12 months for interior applications and every 6 months for exterior, coastal, or industrial environments. Look for signs of corrosion, loosening, wear, or mechanical damage.
- Cleaned regularly – remove dirt, salt deposits, and other contaminants with fresh water and a soft brush. In marine or industrial areas, rinse every 1–3 months to reduce corrosion risk. Avoid harsh abrasives or acidic cleaners.
- Retightened when necessary – check and tighten fixings to the correct torque, ensuring threads are not stripped and substrates are not damaged.
- Protected from dissimilar metals – avoid direct contact with incompatible metals that may cause galvanic corrosion. Where unavoidable, use a suitable barrier such as nylon washers, sealants, or protective coatings.
- Repaired or replaced immediately – if the fastener shows significant corrosion, distortion, head damage, or thread wear, it must be replaced with an equivalent or higher-grade product.
- Maintained after building work – following construction or renovation, clean off all swarf, concrete splatter, and debris to prevent localised corrosion.
- Protected from aggressive environments – for installations near swimming pools, fertiliser storage, or chemical plants, additional cleaning and protective coatings may be required.
- Documented – for critical structural applications, keep a maintenance record including inspection dates, actions taken, and replacement details.



SD Aluminium Roofing Screws Range

BPIR Declaration

Company Information

Legal name of the manufacturer: SD Aluminium Ltd
Manufacture location: New Zealand
Manufacture address for service: 6 John Glenn Avenue, Rosedale, Auckland 0632
Manufacturer NZBN: 9429047563094
Manufacture website: www.sdalu.co.nz/



Branch Locations & Contact Details

Auckland Rosedale Branch

Address: 6 John Glenn Avenue, Rosedale, Auckland 0632
Email: info@sdalu.co.nz
Phone: 09 - 218 2188
09 - 218 2111

Auckland Manukau Branch

Address: 28 Ryan Place, Manukau City, Auckland 2104
Email: info.manukau@sdalu.co.nz
Phone: 09 - 217 8666