

Synthetic Turf Solutions



Contact Us Now!

Auckland Rosedale Branch

Address: 6 John Glenn Ave, Rosedale, Auckland 0632

Phone: 09 - 218 2188

09 - 218 2111

Website: www.sdalu.co.nz

Email: info@sdalu.co.nz

Auckland Manukau Branch

Address: 28 Ryan Place, Manukau City, Auckland 2104

Phone: 09 - 217 8666

Website: www.sdalu.co.nz

Email: info.manukau@sdalu.co.nz

Christchurch Wigram Branch

Address: 67 Vickers Road, Wigram, Christchurch 8042

Website: www.sdalu.co.nz

Email: info.chch@sdalu.co.nz

Follow Us on Social Media



Premium synthetic turf
Natural look with lasting performance

2025-2026 Edition

www.sdalu.co.nz

Synthetic Turf Solution




Premium Lawn Turf




AT30

Pile Height: 30mm
Width: 3.7m
Roll Length: 20m
Stitch Rate: 150 Stitch/m
Sand Fill: 8-10 kg/m²
Colour: Vine Cyan & Vine Green




AT35

Pile Height: 35mm
Width: 3.7m
Roll Length: 20m
Stitch Rate: 160 Stitch/m
Sand Fill: 8-10 kg/m²
Colour: Mint Green & Matt Olive



AT40

Pile Height: 40mm
Width: 3.7m
Roll Length: 20m
Stitch Rate: 160 Stitch/m
Sand Fill: 8-10 kg/m²
Colour: Amerson Olive & Mineral Green



Precision Putting Turf




AT13GOLF

Pile Height: 13mm
Width: 3.7m
Roll Length: 20m
Stitch Rate: 230 Stitch/m
Sand Fill: 8-10 kg/m²
Colour: Emerald



Turf Accessories



SL436 - Seaming Tape
150mm Width
5m/10m Length Roll



SL451 - Ground Fixing Nails
Ø4.5 x 150mm
Q195 Carbon Steel



SL438 - Turf Adhesive Part A
Base Compound
Weight: 9kg
Colour: Green



SL438 - Turf Adhesive Part B
Hardener
Weight: 1kg
Colour: Brown

Installation Guides

1. Clear existing grass and debris from the area.
2. Compact the ground and prepare a stable base using crushed gravel or sand.
3. Roll out the turf and allow it to relax for 30–60 minutes before cutting.
4. Trim edges and ensure all turf rolls face the same direction.
5. Join seams with Seaming Tape and Turf Adhesive (Part A + Part B, 9:1 mix).
6. Secure turf with Fixing Nails Ø4.5 × 125 mm, spaced 150–200 mm apart.
7. Evenly spread silica sand infill (8 – 10 kg/m²) across the surface.
8. Brush the fibres upright for a natural look and smooth finish.